



CONTINUOUS SIDE SEALER EXPERIENCE IS 600 BM SHRINK WRAPPERS AUTOMATIC

DESCRIPTION

A new packaging system that combines a new design, knowledge and experience in the field of Packaging from the technical field to that of the food.

The continuous side welding machine, Experience IS 600 BM is equipped with a unique packaging system of its kind, ideal for a wide range of products with various sizes and shapes up to a maximum height of 350 mm. It's an automatic packaging machine, driven by brushless engines, which allows reaching high production performance. It can work with all types of film: polyolefin, polyethylene, polypropylene, biodegradable films.

TECHNICAL SHEET

POWER 3,5 KW
VOLTAGE 220 V 50 HZ 1 PH + N + T
LENGTH 2544 MM
HEIGHT 1538 MM
WIDTH 1282 MM
WEIGHT 1000 KG
PPM 70 - 120
PRODUCT DIMENSIONS
W: DA 50 A 500 MM / H: DA 10 A 250 MM / L: INFINITA

EXTRA TECHNICAL FEATURES:

Belt speed : 6 to 30 m / min.
Sealing bar width : 600 mm
Power supply : 230 V 50 Hz 1 Ph + N + T
Installed power : 3 Kw
Working plane : 900 mm +/- 50 mm

Reel of film (centerfolded):

MAX. 750 mm Width

Diameter 350 mm

Overall dimensions: 2544 mm x 1282 mm x H 1538 +/- 100 mm

Net weight: 1,100 kg

Mechanical speed up to 9,000 products / hour.

Functions controlled by PLC and operator panel MITSUBISHI

Touch Screen Mitsubishi

Reel unwinding unit and scrap unwinding unit placed in a front position , for a Simple Film Reel change .

Photocells on the horizontal and vertical direction that allow a perfect reading of any product in function of its format.

Filling control of the scrap with automatic winding and consequent cycle arrest.

Height setting with motorized axis controlled by PLC.

Width setting trough sliding guides, adjustable by handle for a rapid execution of the format change.

Remote Control

CONSUMABLES

Polypropylene, Polyolefin, Polythene, Biodegradable

PNEUMATICS FEATURES:

Pneumatic power: 6 bar constant and dehumidified

Compressed air consumption: 1 N / l per day

OPTIONAL

Electronic System **Allen Bradley** or **Siemens**

Additional sealing bar's height up to 300 mm

Sealing bar for polythene up to 100 microns

Stainless Steel Version

Machine on the left / right

Photocell with cross rays

Reading mark Photocell

Center folding unit

Special welding systems

Customized systems for product's loading / unloading

Labeling / Printing systems

Strippers, pushers and other accessories

Additional customized solutions can be studied together with our STAFF according to industry needs.

ADVANTAGES

Ease of use

Systems for working different materials

Reel loading in a frontal position

Easy and intuitive format change

