



INTERMITTENT SIDE SEALER EXPERIENCE IS 350 3N

DESCRIPTION

Continuous sealer Experience IS 350 3N is a machine with three conveyor belts, suitable for types of products ranging from food, technical and / or cosmetics industry. The cross sealing bar is operated mechanically and follows an intermittent movement.

It is suitable for medium / high production and achieves a performance of 5000 pack per hour. Ideal for small spaces thanks to its compact dimensions.

It can work with this types of film: polyolefin, polyethylene, polypropylene.

TECHNICAL SHEET

| | |
|--------------------|--|
| POWER | 3,5 KW |
| VOLTAGE | 220 V 50 HZ 1 PH + N + T |
| LENGTH | 2232 MM |
| HEIGHT | 1400 MM |
| WIDTH | 990 MM |
| WEIGHT | 1100 KG |
| PPM | 55 - 70 |
| PRODUCT DIMENSIONS | W: 30 - 250 MM / H: 0 - 200 MM / L: no limit |

EXTRA

TECHNICAL FEATURES:

| | |
|------------------------|-------------------------------------|
| belt speed | 6 to 30 m / min. |
| working plane | 900 mm +/- 50 mm |
| Sealing bar width | 350 mm |
| Reel of film dimension | max. 450 mm diameter 350 mm Width |
| Technology | Intermittent |

Function controls with PLC and operator panel MITSUBISHI

Touch Screen Mitsubishi

Reel unwinding and scrap unwinding placed in front position, for a fast change of the film reel.

Photocells on the horizontal and vertical direction that allow a perfect reading of any product in function of its format.

Filling control of the scrap film reel with automatic winding and consequent cycle arrest.

Height setting, with motorized axis controlled by PLC.

Width setting with sliding guides, adjustable by handle for a rapid execution of the format change.

Remote Control

Film

Polypropylene, Polyolefin, Polythene, Biodegradable

PNEUMATICS FEATURES:

Pneumatic power: 6 bar constant and dehumidified

OPTIONAL

Electronic System **Allen Bradley** or **Siemens**

Additional sealing bar's height up to 300 mm

Sealing bar for polythene up to 100 microns

Stainless Steel Version

Machine on the left / right

Photocell with cross rays

Reading mark Photocell

Center folding unit

Special welding systems

Customized systems for product's loading / unloading

Labeling / Printing systems

Strippers, pushers and other accessories

Additional customized solutions can be studied together with our STAFF according to industry needs.

ADVANTAGES

Reduced maintenance

Ease of use

Systems for working different materials

Reel loading in a frontal position

Easy and intuitive format change

